



\*ALL EXTERNAL PIPING MUST BE INDEPENDENTLY SUPPORTED.

\*ONLY BASE FITTINGS TO BE LEFT INSTALLED AT TIME OF SHIPMENT PER SII PROCEDURE.
\*TANKS ORDERED WITH FOAM INSULATION WILL HAVE AN INCREASED DIAMETER OF 4-6 INCHES.

\*Consult Snyder's Guidelines for Use and Installation prior to delivery. Available on-line at http://www.snyderindustriestanks.com/Technical

ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE. ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A  $\pm$  3% TOLERANCE.

	DO NOT SCALE	DRAWN BY	OT CHANCE	TITLE
STATUS:	Released	IGG	INDUSTRIES	
© SNYDER INDUSTRIES, LLC, 2019				
ALL DIMENSIONS, DESIGNS, AND INFORMATION ON THIS PRINT MUST BE CONSIDERED PROPRIETARY TO SNYDER INDUSTRIES, LLC, AND MAY NOT BE USED, COPIED, OR BISTRIBUTED WITHOUT WRITTEN PERMISSION OF AN OFFICER (OR HIS AGENT) OF THE FIRM.			(402) 467-5221 www.snydernet.com	PARI

**ASM COVER 22IN SEALED OPEN TOP TKS** 

RT NO. 34701246

D002827

REVISION

Α SHEET

1 OF 1